



JME Holemaker III

Endurance magnetic base drill up to 1-3/8 in [35 mm]

The optimal drilling solution with high powered German motor designed for use with Carbide and HSS cutters for toughest jobs and applications.

Product number: 7 270 59 61 09 0

Details

- Extemely wear resistant concept with durable newly designed polyurethane motorhousing for use in industry and manual trades.
- > Externely lightweight drill yet powerful enough for heaviest drilling applications.
- > Cost effective drill for use with Carbide cutters which offer longer life, higher cutting rate and capable of cutting harder materials. Also running with standard HSS cutters with great results.
- > Optimum power-to-weight ratio.

- > Integrated coolant tank.
- Drill motor does not start for material thicknesses less than 3/16 [4] in[mm] if the magnetic holding force is too low.
- > Pivoting motor cable.
- > Higher RPM for optimal use with carbide cutters.
- > Hand feed wheel can be mounted either side.
- > Integrated hexagon socket holder.

Price includes

- 1 coolant tank
- 2 pilot pins
- 2 hexagonal socket keys, 5 and 6 mm
- / 1 safety strap
- 1 chip guard
- 1 hexagonal socket key with Tgrip, 5 mm

🧹 1 case

Product feature

 Hand feed wheel can be mounted on either side

Application



 \star well suitable

Mag base drilling n	netal up to 1-	3/8 in dia
---------------------	----------------	------------

Twist drills with drill chuck

Performing overhead work

Installation work

Workshop jobs

Technical data

TECHNICAL DATA

Power consumption

Power output

Full load speed

No load speed

Carbide cutter max. dia.

HSS cutter max. dia.

Cutter max. drilling depth

Twist drill max. dia.

Cutter holder

Stroke

Total stroke range

Magnetic holding force

Magnetic holding force

	**	
	**	
	**	
	**	
	**	
★ suitable		

1,100 W	
510 W	
450 rpm	
590 rpm	
1-3/8 [35] in[mm]	
1-3/8 [35] in[mm]	
2 [50] in[mm]	
5/8 [16] in[mm]	
3/4" Weldon	
5-11/16 [145] in[mm]	
10-1/4 [260] in[mm]	
2810 [12,500] lbs[N]	
12,500 N	



Magnetic base dimensions

Magnetic base dimensions

Cable with plug

Weight

Weight

7-11/16 [195] x 3-9/16 [90] in[mm]

195 x 90 mm

8.9 [2.7] ft[m]

25.79 [11.70] lbs[kg]

25.79 lbs

Application examples







